

PICK 'N SPRAY EMULSION SPRAYER



OPERATOR COMFORT

ALL IN ONE MODULE

The emulsion tank including all components of the spray system including the engine and hydraulics are built into one compact module that can be easily installed on pickup truck, mini truck or tractor.

IN CAB CONTROLS

The complete spray system can be operated from inside the cab including separated nozzle control for various spray application and fine end adjustments.

QUICK SET UP

Emulsion can be loaded in under 15 minutes. The spray bars are quickly unfolded for spraying during spray mode.

APPLICATION MODE

The emulsion can be sprayed using the spray bar or using hand lance depending on the requirement



HIGH QUALITY

HOMOGENEOUS MIX

The emulsion is always maintained at the optimum temperature for spraying using automated temperature control heating unit in combination with the tank insulation and continuous circulation.

PRECISE SPRAY RATE

The emulsion flow rate is controlled using a pump which provides operator precise control over the spray rate.

DROP LESS PURGE

Compressed air pushes back the emulsion back to the tank without even a drop of emulsion falling on the ground.

PICK 'N SPRAY		
LOADED MASS	kg	1200
	lbs	2646
OPERATING WIDTH	mm	2400
	in	95
TANK CAPACITY	l	600
	gal	159
MAX SPRAY SPEED	km/h	5
	mph	3
SPRAY RATE	g/m3	100-500
NOZZLES	units	12
DRIVE UNIT		Honda GX200

