



TECHNICAL DATA

MASSES

Operating mass	99 kg
Basic mass	97 kg

DIMENSIONS

Working width	500 mm
---------------	--------

COMPACTION

Frequency	93 Hz
Centrifugal force	19 kN
Amplitude	1.2 mm

TRACTION

Max. gradeability	33 %
Max. working speed	22 m/min

ENGINE

Manufacturer /Model	Honda GX160
Emissions according to	Stage V/CARB P3
Type	Air cooled, petrol
Number of cylinders	1
Fuel consumption /h, avg.	1.4 l
Fuel tank capacity	3.10 l
Power	3.6 kW @ 3600 rpm

DRIVE SYSTEM

Drive system	Mechanical
--------------	------------

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.



DIMENSIONS



DIMENSIONS

H. Height	630 mm
H1. Height, standard handle	990 mm
H2. Height, standard handle	980 mm
L1. Length, standard handle	970 mm
H1. Height, comfort handle	990 mm
H2. Height, comfort handle	980 mm
L1. Length, comfort handle	1070 mm
L. Length	610 mm
W. Basic plate width	500 mm

STANDARD FEATURES

- Highly wear resistant base plate
- Automatic decompression
- All around protection for V-belt
- Protection frame for powerpack
- Recoil starter
- One point lift
- Low HAV handles

OPTIONAL EQUIPMENT

- Water sprinkler system 11l (+2.5kg)
- Comfort handle
- Puncture proof transport wheels (+2kg)
- Block paving mat
- Service Kit

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.